



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
--	---------------------------	--	----------------------	--	-------------------

TECHNICAL DATA	STD
EXTERNAL DIMENSIONS	
width	400 mm
depth	495 mm
height	585 mm
WEIGHT	
	28 kg
VOLTAGE	
	230V 50Hz
POWER REQUIRED	
	2590 W
WATER HARDNESS	
	2-8 °F
INLET WATER PRESSURE	
	200-400 kPa
CROCKERY DIMENSIONS	
plates diameter	--- mm
dishes max. height	195 mm
RACK DIMENSIONS	
	350X350 mm
RACK EQUIPMENT	
	2X10730- 1X10728 - 1X15060
WASHING CYCLES (s)	
	1 (120)
WATER SUPPLY 55°C	
racks/h(*) ⁽¹⁾	30
WATER SUPPLY 10°C	
racks/h(*) ⁽¹⁾	18
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	
	1.4 L
BOILER CAPACITY	
	2.5 L
BOILER HEATING ELEMENT	
	2400 W
RINSING TEMPERATURE (SET)	
	85°C
TANK CAPACITY	
	9.5 L
TANK HEATING ELEMENT	
	1250 W
TANK TEMPERATURE	
	55°C
PUMP POWER	
	190 W (120 L/min ^{***})
DRAIN PUMP (optional)	
	25 W h MAX drainig 0.8m (40 L/min ^{***})
NOISE	
	60.6±0.7 dB(A)

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.